46' Walk Around 7 Marine

Length, overall (L.O.A.) 50'

Beam, overall (B.O.A.) 15' 6"

Deadrise (at transom) 12.5°

Draft (G) 3'

Displacement (standard fuel load)

(D)(G)

30,000 pounds

Fuel capacity (B) 800 gallons

Water capacity (B) 38 gallons

Holding tank capacity (B)

12 gallons

Cockpit area

138 square feet

CONSTRUCTION

- Ablative/Copolymer blue anti-fouling bottom paint, 2 coats, primed
- Alexseal painted engine room and lazzarette for enhanced visibility and easier maintenance
- Blister resistant modified epoxy resin in entire hull skin
- Custom blended vinylester resin used in structural laminates, top-sides, bridges, and hardtops
- High performance isophthalic gelcoat npg superior gloss, flexibility and outstanding weathering characteristics
- Molded fiberglass construction using premium vinylester resins; biaxial & triaxial stitched fabric reinforcement; cored construction
- Vacuum Infused Resin (VIR) construction
- Aluminum fuel tanks with baffles inside; sealed with coal tar

- Molded fiberglass bridge deck/engine room ceiling with foam core for acoustical and thermal insulation
- Non-skid applied for traction and durability
- Stringers, fiberglass / carbon encapsulated foam
- Vacuum Infused Resin (VIR) foam cored bulkheads – Main engine room bulkheads, lazzerette and anchor locker bulkheads

MECHANICAL

- Air conditioning direct expansion zoned with reverse cycle heat for complete climate control throughout the interior
- Bilge pumps linked into monitoring system and connected to float switches for automatic and manual operation
- D/C pressurized fresh water system with on deck fresh water fill and cockpit dockside supply inlet with pressure reducing valve

- Dockside and overboard pump out for holding tank
- Engines, 3 Seven Marine model 557 bracket mounted
- JMS joystick manuvering system for low speed maneuvering and docking
- Smart Command Controls with Digital 7" LCD Touch Screen Multi-Function Gauge
- Trim tabs with auto trim control
- Custom engineered pump room ventilation system with supply and discharge fans for proper fresh air supply and water intrusion suppression from Livos Technologies
- Fresh water supply in pump room for general maintenance and cleaning
- Fuel and oil lines, flexible, steel reinforced USCG approved
- Internal sea strainers for generator, air conditioning and all other sea water pickups – painted white
- Muffler generator, lift muffler with gas water

- separator for cleaner, quieter operation
- PEX plumbing, fresh water system plumbing with manifold system shut off in engine room and forward bilges
- Racor fuel water separators for main engines and generator glass bowl type, top loading for easier maintenance
- Seacocks, bronze, ball-type sea valves and strainers for all thru-hulls below the water line – painted white
- Water heater quick recovery, electric

ELECTRICAL

- 12V DC ship's service throughout
- 12V power supply with breakers on flybridge for future electronics
- 110V outlet in pump room on forward bulkhead
- Anchor light/navigation lights
- Batteries, (3) independent 12V banks mounted in storage boxes

- Battery chargers (2) with thermal cutoff and switching system for complete integration
- Battery distribution panel with battery cutoff and charging system breakers
- Battery parallel system for main engines and generator start
- Bonded electrical system with ground plate
- Engine room lights, DC with switch at helm
- Generator (F), Diesel 11kW
 E-QD (electronic quiet diesel)
 Series, user-friendly with
 electronic frequency control
- Instrument panel lights for main electric panel
- Lighting, overhead recessed in ceiling and rope type décor lights, 12V throughout
- Master electrical control panel located in salon with 12V/120V circuit breakers, individual switching for shore 1, or generator supply and gauges for electrical supply,

- voltmeter, amp meter, and frequency
- Receptacles, 120V duplex with GFCI throughout

BRIDGE DECK

- Wrap-around windshield
- Controls: Top-mounted single lever electronic controls with station select and keypad
- Tackle room access hatch with ladder to engine room
- Helm seat Bluewater Chairs teak ladder back with S.S. pedestal and removable cushions
- Instrumentation based on standard engine package
- Insulated drink box with lid located in starboard aft cabinet
- Lighted compass, flushmounted on centerline
- Manual engine shutdown switches at helm console
- deck for traction and durability
- Port and Starboard bench seating with vinyl cushions and lift tops with storage underneath

- Recessed electronics box in console for custom electronics package that is easily viewable and protected from the elements by acrylic fitted lids with gaskets and stainless steel gas pistons tapped into lids and push knot catches
- Trim tab control switch mounted at helm

COCKPIT

- Dockside electric connection 50 amp/220V electric, located under gunwale
- Pump room access hatch
- Dockside water connection with pressure reducing valve under gunwale
- 2 Fresh water wash downs with hose bib located forward & aft
- Gaskets for all lids, doors, and access doors
- Indirect rope lighting under coaming
- Laminated mounting plate indeck for future fighting chair
- Lazarette hatch for inspection of aft bilge

- Molded-in insulated fish boxes, port & starboard with hatches and drains plumbed to macerator pump-out
- Non-skid deck
- Pop up, stainless steel cleats
- Rod holders, (12)
- Sea water wash down with pump in lazzeratte and supply under forward and aft gunwale to keep deck clean while fishing
- Self bailing cockpit with large cockpit scuppers
- Stainless steel gas springs on all hatches and lids
- Two piece transom door

CABIN and **GALLEY**

- Air conditioning with reverse cycle heat
- Amtico flooring, vinyl
- Fresh water gauge
- Lighting, overhead recessed in headliner
- Main electrical service panel, AC/DC, backlit for easier viewing
- Majilite headliner, natural color, 1/8" foam & tricot backing

- Custom door to bridge deck
- V berth with storage below
- Electric 2 burner surface mount stove
- Exhaust fan, high velocity
- Galley countertop, bone-color Avonite
- Microwave/convection oven located in upper galley cabinet
- Refrigerator/freezer, large capacity, side by side doors
- Sink, stainless steel recessed in countertop with chrome galley faucet
- Storage cabinets and drawers in lower galley, varnished doors and faces with stowage for, utensils, and other items.
 Finished maple interior

HEAD

- Air conditioning/heat with vent in soffit
- Exhaust fan with vent in soffit
- Lights, recessed in soffit and in ceiling
- Linen storage
- Molded fiberglass vanity and sink with Avonite top and chrome faucet

- Receptacle, 120V
- Tecma with overboard and holding tank discharge
- Chrome shower fixtures and with drain to automatic sump pump in bilge
- Towel bar chrome

HARD TOP

- 1/2 tower (hardtop) single pipe bar with molded hardtop
- 3 degree forward angle radar pod
- Anchor, red/green running and stern lights molded (led) U.S.C.G. certified
- Tri color red, white and blue hardtop lights (5)
- Spreader lights 2 in 1 molded LED 12/24 volts
- Rupp Carbon Fiber Fixed 20' double rigged poles
- Rupp Z30 top gun / radial elbows
- 3- side hard enclosure (7 panels center to attach to hardtop)
- Aft enclosure strataglass with roll up door
- Eight rod holders aft legs and top

MISCELLANEOUS

- Anchor constructed with a high-tensile, corrosion resistant aluminum magnesium alloy
- Anchor locker with access from foredeck
- Anchor rode
- Fire extinguishers (3)
- Dock lines, braided nylon (6)
- Stainless steel pop up bow, spring and stern cleats thrubolted to aluminum stainless plates
- Standard Décor package
- Custom delivery kit: life jackets (6 adult), life ring, (21"), flare kit, fenders: 10"
 (2), deck mop, deck brush, bucket, hose, nozzle, emergency horn, first-aid kit and bell
- Zinc on transom

OPTIONAL EQUIPMENT(A) (C) (E)

(A)(C)(E)

STANDARD POWER: Triple 7 Marine Outboards 557 hp each

COCKPIT

Teak Cockpit Decking	19,754
Teak Covering Boards	4,550
Teak Coaming Boards	6,110
Fitting and pump for on-deck	
livewell	1,850
Window in Live well	2,335
Two piece transom door	2,000
Transom custom lettering	POR
Transom std. lettering	1,075

DECK/EXTERIOR

Teak Toe Rail	12,350
Teak Transom	11,050
Boot Stripe	N/C
Black, Blue, Green	
Bottom Paint	N/C
Black, Blue, Green	
Hull color - other than white	13,350
Ice Blue	
Aqua Mist	
Fighting Lady Yellow	
Windlass w. Plow Anchor	9,650

DÉCOR(S)

Custom décor (E)	POR
Décor gallery accessory kit	POR
Wallcovering, custom	POR

BRIDGE DECK

Air conditioning	12,925	
Electronic single lever controls for		
standard helm pod	2,425	
Custom Teak helm pod w/ stainless		
steel wheel Electronic single lever		
controls	3,475	
Teak Bridge Decking	8,710	
Teak Hand Rail	10,400	

GALLEY

Avonite, bone standard	N/C
Avonite, White	750
Avonite, Oat	750
Avonite, Rainforest	750

ENGINE ROOM

Upgrade to 13.5kW genset	2,350
Oil changing system for main	engines
and generator	2,295
Water maker, 350 GPD w/ aut	to back
flush and remote	15,353
Eskimo Ice Maker-250lb/day	12,561

OPTIONAL POWER - POR

• Triple 7 Marine Outboards 557 hp each

NOTES

- A. The right is reserved to make changes, without notice, at any time, in equipment, materials, prices, and specifications. Line drawings and photos may show some optional equipment
- **B.** Capacities of tanks are estimates and usable volume will vary depending upon conditions.
- C. These prices apply only if order is placed prior to boat going into production. Prices are for standard installation only. Custom work is extra cost and may effect delivery schedule.
- **D.** Weight shown is calculated with standard fuel and water tanks full.
- **E.** Includes credit for standard.
- **F.** Generator is not intended to supply power for all standard and optional accessories. Loading must be limited to generator output rating.
- **G.** Measured with largest engines available, standard fuel, and water.