



390 Walkaround Outboard Specifications

Effective September 1, 2021 thru December 31, 2022



390 Walkaround Outboard

Length, overall (LO.A. w/engines)
41'

Beam, overall (B.O.A.) 11' 4"

Deadrise (at transom) 14.5°

Draft 2'5" Engine Down 3'3"

Displacement (Standard Fuel Load)
18,000 pounds

Fuel capacity standard 400 gal

Water capacity 25 gal

Holding tank capacity 5 gal

Cockpit area 80 square feet

CONSTRUCTION

- Ablative/Copolymer anti-fouling bottom paint, 2 coats, primed
- Awlgrip pump-room, lazarette, forward bilge and anchor locker for enhanced visibility and easier maintenance
- Blister resistant modified epoxy resin in entire hull skin
- Custom blended modified vinylester and polyester resin used in structural laminates, topsides, bridges, and hardtops
- Dockside and overboard pump outs for holding tank
- Fiberglass side thru hulls
- Satin interior finish throughout
- High performance isophthalic gelcoat npg superior gloss, flexibility and outstanding weathering characteristics
- Hull vacuum bagged using Airex foam cores with Aramid and E-glass hybrid fiberglass laminates
- Hull interior isophthalic gelcoat topcoat with
- Durable high gloss polyurethane coating

- Aluminum fuel tank and molded freshwater and holding tanks
- Nonskid for traction and durability
- Stringers, fiberglass encapsulated foam
- Vacuum infused composite bulkheads

MECHANICAL

- Air Conditioning - direct expansion zoned with reverse cycle heat
- Bilge pumps with additional clean out pumps on centerline linked into monitoring system and connected to switches for automatic and manual operation
- DC power-assist hydraulic steering
- Pump room ventilation
- Fire suppression system
- Fuel lines, flexible, steel reinforced USCG approved aircraft type.
- Internal sea strainers for generator
- Muffler - generator/lift muffler with gas water separator for cleaner, quieter operations
- PEX plumbing, freshwater system with manifold system shut off
- Pressurized freshwater system, 12V D/C pump with on deck freshwater fill and cockpit dockside supply inlet with pressure reducing valve
- Racor fuel water separators for main engines and generator includes vacuum gauge for fuel filter restriction
- Seacocks, stainless steel, ball-type sea valves and strainers for all thru-hulls below the water line
- Trim tabs, single piston with individual controls
- Water heater, quick recovery, electric

ELECTRICAL

- 12V DC ship's service throughout
- 12V power supply with breakers on flybridge for future electronics
- Anchor light/navigation lights
- Batteries, (4) independent 12V banks mounted in fiberglass

- storage box
- Battery chargers with thermal cutoff and switching system for complete segregation
- Battery distribution panel with battery cutoff and charging system breakers
- Bonded electrical system with ground plate
- Color-coded, labeled wiring system with corresponding drawings
- LED interior lighting throughout
- Emergency DC crossover
- Shore power cable with 3 wire grounded cord, 30 amp/220V inlet with 50' cord
- Instrument panel lights for main electric panel
- Receptacle, 120V duplex with GFI throughout

BRIDGE DECK

- Pump room access through hatch in bridge deck
- Helm seat, teak ladder back with 4' pedestal and removable cushions and covers
- Instrumentation & controls based on standard engine package
- Lighted compass flush mount on centerline
- Nonskid deck for traction and durability
- Port and starboard side bench seating vinyl cushions and storage underneath

COCKPIT

- Dockside water connection with pressure reducing valve under forward gunwale
- Freshwater wash down with hose bib located under forward gunwale
- Gaskets for all lids, doors and access doors
- Indirect rope lighting under coaming
- Backing plate in deck for fighting chair or table
- Lazarette hatch with access to steering, trim tabs, drains and pumps
- Two insulated ice boxes
- Stainless steel cleats
- Rod holders, (4) flush mounted

- Seawater wash down under gunwale
- Self bailing cockpit with large cockpit scuppers
- Stainless steel gas pistons, all hatches and lids

LOWER CABIN & GALLEY

- Air conditioning with reverse cycle heat
- Over / under bunks with storage underneath
- Main electrical service panel, AC/DC
- Countertop, high gloss bone color Corian
- Lights, overhead LED
- Microwave oven in cabinet
- Refrigerator, drawer type under-counter

- Sink w/ S.S. faucet

HEAD

- Countertop, one-piece molded bone Corian with rounded edges and with sink
- Electric head plumbed with y-valve for overboard discharge or direct to holding tank
- Exhaust fan with vent
- Flooring, nonskid
- Bath towel storage
- Lower vanity with fiberglass door
- Lights, overhead LED
- "Wet head" shower, fiberglass with satin chrome shower fixtures and with drain to automatic sump pump in bilge
- Towel bar and ring

MISCELLANEOUS

- Anchor - constructed with a high-tensile, corrosion resistant aluminum magnesium alloy
- Anchor locker with access from foredeck
- Anchor rode
- Fire extinguishers (2)
- Magnetic switches for lights in all forward bridge compartments
- Mooring lines, braided nylon (6)
- Stainless steel bow, spring and stern cleats thru-bolted to aluminum backing plates
- Water delivery kit with tool set (H)

NOTES: This specification sheet is subject to change. The right is reserved to make changes, without notice, at any time, in equipment, materials, prices and specifications. Line drawings and photos may show some optional equipment

- A. The right is reserved to make changes, without notice at any time, in equipment, materials, prices and specifications. Line drawings and photos may show some optional equipment
- B. Capacities of tanks are estimates and useable volume will vary depending upon conditions.
- C. These prices apply only if order is placed prior to boat going into production. Prices are for standard installation only. Custom work is extra cost.
- D. Weight shown is calculated with standard fuel and water tanks full.
- E. Seakeeper requires diesel generator package and may reduce fuel capacity
- F. Includes credit for standard.
- G. Must be ordered 90 days prior to start date.
- H. Includes life jackets (6 adult), flare kit, fenders: 10" (2), deck mop, deck brush, bucket, hose, nozzle, fuel filters (2), boat soap (1qt.) and bilge cleaner (1qt.)
- I. Generator is not intended to supply power for all standard and optional accessories. Load must be limited to generator output rating.
- J. Measured with largest engines available, standard fuel, and water
- K. Fuel capacity calculated with Seakeeper prep

POWER OPTIONS

TWIN 350 MERCURY VERADO, TWIN 400 MERCURY VERADO, TWIN 425 YAMAHA, TRIPLE 300 SUZUKI, TRIPLE 300 YAMAHA, TRIPLE 300 MERCURY VERADO

TOWER OPTIONS

WE WORK WITH THE BEST TOWER MANUFACTURERS IN THE WORLD. WE HAVE PUT TOGETHER THREE BASIC PACKAGES FOR OUR 390 WALKAROUND. THERE ARE FAR TOO MANY OPTIONS TO LIST. AFTER WE SPEC A BOAT, WE WILL WORK WITH YOU AND THE TOWER MANUFACTURER TOGETHER TO CUSTOMIZE IT TO BE EXACTLY WHAT YOU WANT

HARD TOP

- Hard Top - molded top
Polished Pipe (2) Antenna Standoff
- Recessed Lights (4),
Lumitec tri-color LED
- Molded 2-in-1 Lumitec
LED spreader light pod aft
- Rod Holder Polished Weld
to Rail behind Hardtop (6)
- Rod Holder Polished Weld
to Aft Legs (2 each side)
- Rupp outriggers (2)
Carbon Fiber with Top
Gun Z-30 Bases
- Nav Lights Port Starboard,
stern Molded
- Enclosure 3 Sided
Strataglass Panels

MARLIN TOWER

- Marlin Tower w/molded
top, No gap, Polished
Pipe, (2) Antenna Standoff
- Recessed Lights (4),
Lumitec tri-color LED
- Control Box 53" w/Flush
Mounted Compass
- Molded 2-in-1 Lumitec
LED spreader light pod aft
- Tower Sunshade Molded
Top Welded Antenna
Mounts
- Rod Holder Polished Weld
to Rail behind Hardtop (5)
- Rod Holder Polished Weld
to Aft Legs (2 each side)
- Rupp outriggers, Single
Spreader, solid back bar
- Recessed lights (2) tri-
color tower sunshade

TUNA TOWER

- Tuna Tower w/molded top
Walkaround 6' gap,
Polished Pipe, (2) Antenna
Standoff
- Recessed Lights (4),
Lumitec tri-color LED
- Molded One Piece
Standing Platform with
molded box
- Molded 2-in-1 Lumitec
LED spreader light pod aft
- Control Box 53" w/Flush
Mounted Compass
- Tower Sunshade Molded
Top Welded Antenna
Mounts
- Rod Holder Polished Weld
to Rail behind Hardtop (5)
- Rod Holder Polished Weld
to Aft Legs (2 each side)
- Rupp outriggers, Single
Spreader, solid back bar
- Recessed lights (2 each)
tri-color tower sunshade
& platform

ELECTRONICS & ENTERTAINMENT

THIS AREA IS TOTALLY UP TO THE CUSTOMER. WE WORK WITH SOME OF THE FINEST COMPANIES IN THE INDUSTRY WHO WILL CUSTOMIZE A SYSTEM TO YOUR SPECIFIC NEEDS AND BACK IT UP WITH GREAT SERVICE FOR YEARS TO COME.

ARRANGEMENTS

